

# K832 Cable Datasheet

## SC, OA1 8p, open, 1/4, T

Signal cable between CSM measurement module and strain gauge sensor with quarter bridge completion for 120 Ohm resp. 350 Ohm

### Description

Signal cables are especially manufactured for CSM. They use a robust line and are characterized by a high interference resistance and a good signal quality. The cable is flexible and chemical resistant, including fuel and oil.

### Temperature


The specified temperature range of the main cable excluding connectors is -40 °C to 150 °C. The specified temperature range for connectors may vary depending on the type (e.g. LEMO B connector: -55 °C to 250 °C; D-Sub: -55 °C to 105 °C; Banana: -40 °C to 80 °C; LEMO Redel: -50 °C to 150 °C).

### Bending Radius

5 × Diameter

### Connectors


A OA1                      8-pole              Code: C              male  
 B open



Frontal view connector


### Variants

Item No.	Cable Name	Length
ART1421002	K832-0200 /120	2 m
	l1: 1 m                      l2: 1 m	
ART1421003	K832-0200 /350	2 m
	l1: 1 m                      l2: 1 m	
ART1421004	K832-0500 /120	5 m
	l1: 4 m                      l2: 1 m	
ART1421005	K832-0500 /350	5 m
	l1: 4 m                      l2: 1 m	
ART1421007	K832-1000 /350	10 m
	l1: 9 m                      l2: 1 m	



Picture similar to actual product

### Overview



## Pinning

Con. A Pin	Signal	Cable Wire Color	Circuit	Con. B Wire Color
1	VIN-	purple		purple
2	VIN+	blue		-
3	VOUT-	pink		pink
4	VOUT+	red		red
5	VSENSE-	grey		-
6	VSENSE+	green		-
7	Channel shield	Drain wire		Drain wire
8	Data **)	yellow		-
Housing	Cable shield	-		-
			<p><b>Channel shield = drain wire</b></p>	

\*) R is 120 resp. 350 ohm, depending on ART

\*\*) Only for measurement modules with TEDS support



**CSM GmbH Headquarters** (Germany)

Raiffeisenstraße 36 • 70794 Filderstadt

☎ +49 711- 77 96 40 ✉ sales@csm.de

**CSM Office Southern Europe** (France, Italy)

Site d'Archamps

60, rue Douglas Engelbart • Immeuble ABC 1, Entrée A – 1er étage

74160 Archamps, France

☎ +33 450-95 86 44 ✉ info@csm-produits.fr

**CSM Products, Inc. USA** (USA, Canada, Mexico)

1920 Opdyke Court, Suite 200 • Auburn Hills, MI 48326

☎ +1 248 836-4995 ✉ sales@csmproductsinc.com

**CSM** (RoW)

**Vector Informatik** (China, Japan, Korea, India, Great Britain)

ECM AB (Sweden)

DATRON-TECHNOLOGY (Slovakia, Czech Republic)

Our partners guarantee you worldwide availability.

Feel free to contact us.

CSM GmbH Germany is certified.



All trademarks mentioned are property of their respective owners.

Specifications are subject to change without notice.

CANopen® and CiA® are registered community trademarks of CAN in Automation e.V.

EtherCAT® is registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany..