

K206 Cable Datasheet

PC, LOB 5p, open

Power supply cable for UniCAN 2, including Key-On (K15 ignition)

Description

System cables are especially manufactured for CSM. They are designed for high interference resistance and a very low internal resistance of the supply lines. The cable is flexible and chemical resistant, including fuel and oil.

Temperature

The specified temperature range of the main cable excluding connectors is -30 °C to 150 °C. The specified temperature range for connectors may vary depending on the type (e.g. LEMO B connector: -55 °C to 250 °C; D-Sub: -55 °C to 105 °C; Banana: -40 °C to 80 °C; LEMO Redel: -50 °C to 150 °C).

Variants

Item No.	Cable Name	Length
ART0650056	K206-0100	1 m




Picture similar to actual product

Bending Radius

5 × Diameter


Connectors

A LEMO 0B 5-pole Code: G male **B** open



Frontal view connector

Overview



Pinning

Con. A	Cable	
Pin	Signal	Wire Color
1	Power +	red
2	Power GND	black
5	K15	grey
Housing	Cable shield	-
3, 4 n.c.	-	-



CSM GmbH Headquarters (Germany)

CSM Office Southern Europe (France, Italy)

Site d'Archamps
60, rue Douglas Engelbart • Immeuble ABC 1, Entrée A – 1er étage
74160 Archamps, France
\$\display +33 450-95 86 44 \omega info@csm-produits.fr

CSM Products, Inc. USA (USA, Canada, Mexico)

CSM (RoW)

Vector Informatik (China, Japan, Korea, India, Great Britain)
ECM AB (Sweden)
DATRON-TECHNOLOGY (Slovakia, Czech Republic)

Our partners guarantee you worldwide availability. Feel free to contact us.

CSM GmbH Germany is certified.



All trademarks mentioned are property of their respective owners.

Specifications are subject to change without notice.

CANopen® and CIA® are registered community trademarks of CAN in Automation e.V.

EtherCAT® is registered trademark and patented technology, licensed by Beckhoff

Automation GmbH, Germany.