

XCP-Gateway pro



Product description

The protocol converter **XCP-Gateway pro** is especially designed for the CSM EtherCAT® measurement module series and has been developed for measurement tasks with numerous measurement channels and high measurement data rates. The **XCP-Gateway pro** allows the linking of CSM EtherCAT® measurement devices to the data protocol XCP-on-Ethernet, thus combining the advantages of data acquisition via EtherCAT® with the flexibility of the wide-spread standard XCP-on-Ethernet. In addition, temperature information from CSM HV Breakout Modules can be transferred via EtherCAT®.

XCP-Gateway pro features two CAN interfaces for connecting CSM CAN bus measurement modules, allowing the integration of their measurement data into the protocol XCP-on-Ethernet.

All measurement modules receive their power supply from the **XCP-Gateway pro**. The configuration of both EtherCAT® and CAN measurement modules is done in CSMconfig.



Key features

- ▶ EtherCAT® to XCP-on-Ethernet converter
 - ▶ EtherCAT®: time synchronization of all measurement signals better than 1µs
 - ▶ XCP-on-Ethernet: accuracy of measurement signal time stamps is 1µs
- ▶ Suited for 4.5 million data points per second (MS/s), e.g. four channels with 1MHz
- ▶ Autonomous master for CSM EtherCAT® devices of the measurement module series
- ▶ 2 CAN interfaces for connecting CSM CAN bus measurement modules
- ▶ Simple configuration of XCP-Gateway pro and connected measurement modules via CSMconfig

Scope of delivery

- ▶ XCP-Gateway pro
- ▶ Configuration software CSMconfig
- ▶ Documentation

Accessories

- ▶ See datasheets "XCP/ECAT Accessories" and "CAN Accessories"

Technical data

Type designation	XCP-Gateway pro
PC	
Physical layer	Ethernet 100Base-TX, 100 MBit/s
Protocol	XCP on UDP/IP
ECAT	
Physical layer	Ethernet 100Base-TX, 100 MBit/s
Protocol	EtherCAT®
CAN	CAN 2.0B (active), High Speed (ISO 11898-2:2016), 125 kbit/s to 1 Mbit/s for connecting CAN-based CSM measurement modules
Configuration	via CSMconfig, settings are stored in the device
Power supply	
Minimum	6 V DC (-10 %)
Maximum	50 V DC (+10 %)
Power consumption	typ. 2 W
LED Ethernet	Link/Activity PC (green)/Link/Activity ECAT (green)
LED Status	2 multi-colored LEDs for DEV and ECAT
LED CAN/PWR	interface activated (green)
Housing	aluminum, silver anodized
Protection class	IP67
Weight (device)	approx. 400 g
Dimensions (w × h × d)	approx. 200 × 40 × 50 mm (Slide Case)
Connectors ¹	
PC (Ethernet/power supply)	LEMO 1B, 8-pole, code L
ECAT (EtherCAT®/power supply)	LEMO 1B, 8-pole, code A
CAN/PWR	LEMO 0B, 5-pole, code G
Sync	LEMO 0B, 2-pole, code G (galvanically isolated)
Operating and storage conditions	
Operating temperature	-40 °C to +85 °C
Relative humidity	5 % to 95 %
Pollution degree	3
Storage temperature	-55 °C to +90 °C
Conformity	CE

¹ Optionally available in other variants.



CSM GmbH Headquarters (Germany)

Raiffeisenstraße 36 • 70794 Filderstadt

☎ +49 711-77 96 40 ✉ sales@csm.de

CSM Office Southern Europe (France, Italy)

ArchParc • Immeuble ABC 1 • Entrée A

60, rue Douglas Engelbart • 74160 Archamps, France

☎ +33 4 50 95 86 44 ✉ info@csm-produits.fr

CSM Products, Inc. USA (USA, Canada, Mexico)

1920 Opdyke Court, Suite 200 • Auburn Hills, MI 48326

☎ +1 248 836-4995 ✉ sales@csmproductsinc.com

CSM (RoW)

Vector Informatik (China, Japan, Korea, India, Great Britain)

ECM AB (Sweden)

DATRON-TECHNOLOGY (Slovakia, Czech Republic)

Our partners guarantee you worldwide availability.

Feel free to contact us.

CSM GmbH Germany is certified.



All trademarks mentioned are property of their respective owners.

Specifications are subject to change without notice.

CANopen® and CiA® are registered community trademarks of CAN in Automation e.V.

EtherCAT® is registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany.