

HV Breakout Module

Type 3.1



Product description

CSM's **High Voltage Breakout Module (HV BM)** Type 3.1 has been designed for **three phase evaluation** of power, current and voltage of cables carrying high voltage with currents of up to $\pm 32 A_{rms}$, such as supplied by public AC- charging stations.

The **HV BM 3.1** is to be inserted into the power supply cable or charging cable by feeding the cable through cable glands into the module and connecting it. Measuring one or up to three phases with only one single measurement device offers enormous cost and space savings.

Voltages in star-configuration are measured directly in the **HV BM 3.1**. Current measurements are performed by shunts. They contain differential amplifiers, a temperature sensor and a memory chip for calibration data for automatic online temperature compensation.

The **HV BM 3.1** outputs per variable the measured data with a maximum data rate of up to 500 kHz via an EtherCAT® interface and simultaneously with a data rate of up to 5 kHz via the additional CAN interface. This allows high speed data acquisition via Ethernet and data recording via CAN data logger at the same time.

Maintenance

- ▶ HV isolation test at least every 12 months, see EN 61010 for scope of testing
- ▶ Calibration every 12 months recommended

Key features



- ▶ Three phase measurement of voltage (U) and current (I) in HV applications, HV-safe enclosed for:
 - ▶ Nominal voltages up to $\pm 1,000 V$ (measurement range up to $\pm 1,000 V$)
 - ▶ Currents up to $\pm 32 A_{rms}$ (rated) (measurement range up to $\pm 50 A$)
- ▶ Calculation of instantaneous power with 500 kHz data rate
- ▶ Output of voltage, current and instantaneous power with up to 500 kHz measurement data rate
- ▶ Simultaneous EtherCAT® and CAN bus communication

Scope of delivery

- ▶ HV Breakout Module 3.1
- ▶ Configuration software CSMconfig
- ▶ Documentation
- ▶ Device Description File (*.xml)
- ▶ Calibration certificates for I and U in accordance with DIN EN ISO/IEC 17025
- ▶ HV isolation test protocol

Accessories

- ▶ See "ECAT Accessories" and "CAN Accessories" datasheets

Technical data


Type designation	HV BM 3.1
	
Installation in	power or charging cable for L1, L2, L3, N, PE, internally connected via Phoenix terminals, cable cross-section 0.2 up to 6 mm ² each
Number of measured phases	3
Number of cable glands	1 (per side)
Cable outer diameter	from 9 mm up to 25 mm
Measurement signals	voltage, current and instantaneous power
Measurement ranges	
Voltage	±50, ±100, ±200, ±500, ±1,000 V
Current	±32 A rated current (I_{rated}) configurable measurement ranges $I_{meas.} = \pm 5, \pm 10, \pm 25, \pm 50$ A
Instantaneous power	values calculated online at 500 kHz
Internal resolution	16 bit
Internal sampling rate	500 kS/s
Measurement data rate/ sending rate	
ECAT	1, 2, 5, 10, 50, 100, 500 kHz ¹
CAN	1, 2, 5, 10, 20, 50, 100, 200, 500 Hz, 1, 2, 5 kHz ²
HW input filter	8 th order Butterworth filter, cutoff frequency approx. 200 kHz
SW input filter	6 th order Butterworth filter, cutoff frequency automatically adjusted to measurement data rate or selectable for voltage, current and instantaneous power ECAT: cutoff frequency up to 100 kHz or at sending rate of 500 kHz SW-filter switchable CAN: cutoff frequency up to 1 kHz, alternatively mean filter
Output signals	
ECAT and CAN	voltage, current, instantaneous power, shunt temperatures, module temperature

Type designation	HV BM 3.1
	
Measurement deviation³	
Voltage	
Gain error at 25 °C	max. ±0.05 % of measured value
Offset and scaling error	max. ±0.02 % of range
Gain drift	max. ±20 ppm/K of measured value
Zero drift	max. ±10 ppm/K of range
Current	online calculation with stored calibration data, with temperature compensation
Measurement error	max. ±0.15 % of measured value
Temperature drift	max. ±0.05 % of range
Fields of application⁴	for measurements in HV environments ⁵
Measurement voltages (unipolar & bipolar)	up to 1,000V peak
Routine test	HV-Isolation test ⁵
EtherCAT® interface	Ethernet 100 Base-TX, 100 Mbit/s EtherCAT® slave controller, synchronization via Distributed Clocks or Sync Manager 3
Configuration	with configuration software CSMconfig via XCP-Gateway or EtherCAT® master software via CANopen over EtherCAT® (CoE), settings and configurations stored in the module
CAN interface	CAN 2.0B (active), High Speed (ISO 11898-2:2016), 125kbit/s to max. 1Mbit/s, up to 2 Mbit/s with appropriate CAN-interface, data transfer free running
Configuration	via CAN bus using CSMconfig, settings and configurations stored in the module
LED indicators	
ECAT	Status/Link Activity IN/Link Activity OUT
CAN	Power/Status
Measurement channels	configuration/operation
Reinforced insulation^{4, 5}	
Channel/channel	1,000 V _{rms}
Channel/ECAT	1,000 V _{rms}
Channel/power supply	1,000 V _{rms}
Measurement categories⁶	
CAT 0	1,000V
CAT II	600V
CAT III	300V

Type designation	HV BM 3.1
	
Power supply	
Minimum	7 V DC (-10 %)
Maximum	30 V DC (+10 %)
Power consumption	typ. 5 W
Housing	aluminum with HV designation (RAL 2003)
Protection class	IP67 ⁷
Ground connection	M8 threaded hole
Weight	approx. 1,000 g (without cable glands)
Dimensions (w × h × d)	approx. 200 × 45 × 100 mm (without cable glands)
Connectors	
EtherCAT®IN	LEMO 1B, 8-pole, code L
EtherCAT®OUT	LEMO 1B, 8-pole, code A
CAN ⁸	LEMO 0B, 5-pole, code G
Power cables	cable glands for power supply cable or charging cable
Operating and storage conditions	
Operating temperature range	-40 °C to +120 °C
Relative humidity	5 % to 95 % (non-condensing)
Operating altitude	max. 5,000 m above sea level (CAT 0) max. 3,000 m above sea level (CAT II and CAT III)
Pollution degree	4 ⁷
Storage temperature	-40 °C to +125 °C
Conformity	CE
Device safety	EN 61010-1:2020+COR1:2022 EN 61010-2-030:2022

Cable glands

Depending on the cable outer diameters, different cable glands must be adapted to the **HV BM 3.3**. Only suitable combinations (cables + cable glands) ensure the tightness of the housing. The cable glands are selected separately as needed. The following types are currently available:

Type	9/14	11/20	15/25
			
Cable outer diameter			
D ₁ maximum	14 mm	20 mm	25 mm
D ₁ minimum	9 mm	11 mm	15 mm
D ₂ maximum	12 mm	17 mm	21 mm

¹ All measurement data rates are configurable via XCP-Gateway. When configuring via a standard EtherCAT® master, a maximum measurement data rate of 10kHz/channel is supported.

² In order to be able to use a measurement data rate of 5 kHz for all measurement signals, a CAN interface with 2 Mbit/s is required.

³ The values of current can differ depending on the frequency. Further information can be found in the Technical Information document on the subject of "Deviation of Measurement".

⁴ Please read the CSM document "Safety Instructions HV Breakout Module"!

⁵ According to EN 61010-1:2020+COR1:2022 with EN 61010-2-030:2022

⁶ Further information can be found in the Technical Information document "Measurement Categories for CSM HV Measurement Modules".

⁷ Only if installed correctly, please follow the assembly instructions in the installation manual.

⁸ Optionally available in other variants.



CSM GmbH Headquarters (Germany)

Raiffeisenstraße 36 • 70794 Filderstadt
☎ +49 711-77 96 40 ✉ sales@csm.de

CSM Office Southern Europe (France, Italy)

Site d'Archamps
60, rue Douglas Engelbart • Immeuble ABC 1, Entrée A – 1er étage
74160 Archamps, France
☎ +33 450-95 86 44 ✉ info@csm-produits.fr

CSM Products, Inc. USA (USA, Canada, Mexico)

1920 Opdyke Court, Suite 200 • Auburn Hills, MI 48326
☎ +1 248 836-4995 ✉ sales@csmproductsinc.com

CSM (RoW)

Vector Informatik (China, Japan, Korea, India, Great Britain)
ECM AB (Sweden)
DATRON-TECHNOLOGY (Slovakia, Czech Republic)

Our partners guarantee you worldwide availability.
Feel free to contact us.

CSM GmbH Germany is certified.



All trademarks mentioned are property of their respective owners.
Specifications are subject to change without notice.
CANopen® and CiA® are registered community trademarks of CAN in Automation e.V.
EtherCAT® is registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany.