



HV PT-TBM 8



Product description

Measurement module **HV PT-TBM 8** features eight measurement inputs in 4-wire-connection for PT100 and PT1000 sensors and has been especially designed for precise temperature measurements in high-voltage environments.

HV PT-TBM 8 is excellently suited for measuring the temperature of individual battery cells and battery packs in high-voltage batteries. Due to the thin-film design of specific foil PT sensors, it is possible to precisely monitor the temperature of battery cells, even under very limited space conditions.

This 19" slide-in module with eight measurement channels has been specifically designed for test bench applications.

Key features

CAN



- ▶ 8 inputs in 4-wire connection for PT100 and PT1000 sensors
- ▶ Individual PT coefficients can be entered for best possible sensor adjustment
- ▶ Reinforced insulation up to 846 V
- ▶ Type approval test according to safety standard DIN EN 61010 by an accredited test laboratory
- ▶ Routine test according to safety standard DIN EN 61010

Shipping content

- ▶ Measurement module HV PT-TBM 8
- ▶ Configuration software CSMconfig
- ▶ Documentation
- ▶ Calibration certificate
- ▶ HV isolation test certificate

Maintenance


- ▶ HV isolation test according to DIN EN 61010 at least every 12 months
- ▶ Calibration every 12 months recommended

Accessories

- ▶ See datasheet "CAN Accessories"



Technical data

Type designation	HV PT-TBM 8 /65
	
Measurement inputs	8 inputs in 4-wire connection for PT100 and PT1000 sensors, configurable via software
Measurement ranges	-50 °C to +100 °C and -100 °C to +500 °C
Internal resolution	16 bit
Internal sampling rate per ch.	8 kHz
Measurement data rate per ch.	1, 2, 5, 10, 20, 50, 100 Hz
HW input filter	4th order Butterworth filter (threshold frequency approx. 5 kHz)
SW input filter	FIR filter (Finite Impulse Response) threshold frequency automatically adjusted to measurement data rate
Linearization	via individual PT coefficients R0, A, B and C
Measurement current	PT100: 500 µA, PT1000: 400 µA
Measurement uncertainty ¹⁾	
Gain error at 25 °C	max. ±0.1 % of measured value
Offset and scaling error	max. ±0.1 K
Gain drift	max. ±10 ppm/K of measured value
Zero drift	max. ±3 mK/K
Reinforced insulation ²⁾	
Channel / channel	846 V
Channel / CAN	846 V
Channel / power supply	846 V
Functional insulation	
CAN / power supply	designed for supply voltages 12 V and 24 V
CAN interface	CAN 2.0B (active), High Speed (ISO 11898-2) 125 kbit/s to 1 Mbit/s, up to 2 Mbit/s with CSMcan interface, data transfer rate free running
Configuration	via CAN bus with CSMconfig settings and configuration date are stored in the device
Power supply	
Minimum	6 V DC (-10 %)
Maximum	30 V DC (+10 %)
Power consumption	typ. 3 W
LED indicator	
CAN	power (green) / status (red)
Measurement channels	valid measurement value (green) / channel selected (green flashing) / deactivated channel selected (red flashing)

Type designation	HV PT-TBM 8 /65
Housing	aluminium with HV designation on the front-side (RAL2003)
Protection class	IP65
Ground connection	M6 threaded hole
Mounting	19 inch
Weight	approx. 735 g
Dimensions (w × h × d)	19 HP (approx. 96 mm) 3 U (approx. 129 mm) 100 mm (+ 25 mm protective bracket)
Connectors	
CAN / power supply	LEMO 0B, 5-pole, code G
Signal inputs	LEMO Redel 2P, 8-pole, code C (grey)
Operating and storage conditions	
Operating temperature range	-40 °C to +85 °C
Relative humidity	5 % to 95 % (non-condensing)
Operating altitude	max. 5,000 m above sea level
Pollution degree	3
Storage temperature	-40 °C to +85 °C
Conformity ³⁾	CE
Device safety	DIN EN 61010

¹ In interference-polluted environments, additional measurement errors can occur.

² For operating the device directly in systems with operation voltages of > 60 V, e.g. high-voltage batteries of hybrid or electric vehicles. Please read the CSM document "Safety Instructions HV PT-TBM"!

³ The measurement modules are designed for cable lengths < 3 m.

additional products

HV PTMM 2

MiniModule HV PTMM 2 is equipped with two measurement inputs in 4-wire connection for PT100 and PT1000 sensors and is especially designed for precise temperature measurements in high-voltage environments. Due to its compact size the HV PTMM 2 is very well suited for measurement applications used under limited space conditions.



HV TH-TBM 8

The HV TH-TBM 8 module belongs to the series of high-voltage measurement modules which have been specifically developed for temperature measurements with type K sensors in the fields of e-mobility (electric and hybrid vehicles). Designed as a 19" slide-in module, it is ideally suited for test bench applications.





CSM GmbH
Computer-Systeme-Messtechnik

Raiffeisenstraße 36 • 70794 Filderstadt • Germany
Phone: +49 711-7 79 64-20 • Fax: +49 711-7 79 64-40
info@csm.de • www.csm.de

