

# HV TH4 evo CAN MM Series



## Product description

The measurement module **HV TH4 evo** is especially designed for safe temperature measurements on live high-voltage parts and is therefore excellently suited for mobile and stationary use in e-mobility applications (electric and hybrid vehicles).

Thanks to their compact and robust design and a very wide operating temperature range, **HV TH4 evo** measurement modules can be installed and operated directly in the engine compartment and other constrained spaces, e. g. close to the high-voltage battery and power electronics. **HV TH4 evo** features a high degree of measurement accuracy over the entire operating temperature range.

## Scope of delivery

- ▶ Measurement module HV TH4 evo
- ▶ Configuration software CSMconfig
- ▶ Documentation
- ▶ Calibration certificate in accordance with DIN EN ISO/IEC 17025
- ▶ HV isolation test certificate



## Key features

- ▶ NiCr-Ni temperature inputs (K type), with reinforced insulation up to 1,000V DC
- ▶ Excellent measurement accuracy for all temperature ranges and environmental conditions
- ▶ Operating temperature range: -40 °C to +125 °C
- ▶ Type approval test and routine test according to safety standard EN 61010


## Maintenance

- ▶ HV isolation test according to EN 61010-1 at least every 12 months
- ▶ Calibration every 12 months recommended

## Accessories

- ▶ See datasheet "CAN Accessories"

## Technical data

<b>Type designation</b>	<b>HV TH4 evo</b>
	
<b>Technical data valid as of revision</b>	C100
<b>Inputs</b>	4 NiCr-Ni (K type)
Measurement range	-270 °C to +1,372 °C
Internal resolution	16 bit
Internal sampling rate per channel	1 kHz
Measurement data rate per channel	1, 2, 5, 10, 20, 50, 100, 200 Hz adjustable per module or per channel via configurable CAN identifier
HW input filter	low-pass filter 150 Hz
SW input filter	FIR-Filter (Finite Impulse Response), averaging automatically adjusted to measurement data rate median11 filter, single or double internal clock rate
Channel-specific comments	free text consisting of up to 100 characters per channel
Broken sensor detection	yes
Cold junction compensation	internal cold junction per channel
<b>Measurement deviation <sup>1</sup></b>	
Gain error at 25 °C	max. ±0.05 % of measured value
Offset and scaling error	typ. ±0.15 K max. ±0.3 K ±12 µV
Gain drift	max. ±10 ppm/K of measured value
Zero drift	max. ±4 mK/K
<b>Fields of application <sup>2</sup></b>	for measurements in HV environments <sup>3</sup>
nominal voltage	up to 1,000V DC
Routine test	HV isolationstest according to EN 61010-1
<b>Reinforced insulation <sup>2, 3</sup></b>	channel/channel; channel/CAN; channel/power supply
<b>Functional insulation</b>	
CAN/power supply	designed for supply voltages 12 V and 24 V

<b>Type designation</b>	<b>HV TH4 evo</b>
<b>Measurement categories <sup>4</sup></b>	
CAT 0	1,000V DC
CAT II	600V
CAT III	300V
<b>CAN interface</b>	CAN 2.0B (active), High Speed (ISO 11898-2:2016), 125 kbit/s to 1 Mbit/s, up to 2 Mbit/s with suitable CAN interface, data transfer is "free running"
Configuration	via CAN bus with CSMconfig or CSM INCA AddOn settings and configurations stored in the device
<b>Power supply</b>	
Minimum	6V DC (-10 %)
Maximum	30V DC (+10 %)
Power consumption	typ. 0.6W
LED indicator	power (green), status (red)
<b>Housing</b>	aluminum with HV designation on the front-side (RAL 2003)
Protection class	IP67
Ground connection	M6 threaded hole
Weight (device)	approx. 350 g
Dimensions (w × h × d)	approx. 130 × 33 × 75 mm/ approx. 130 × 38 × 75 mm (Slide Case)
<b>Connectors</b>	
CAN/power supply <sup>5</sup>	LEMO 0B, 5-pole, code G
Signal inputs	LEMO Redel 2P, 8-pole, code B (grey)
<b>Operating and storage conditions</b>	
Operating temperature range	-40 °C to +125 °C
Relative humidity	5 % to 95 % (non-condensing)
Altitude	max. 5,000 m above sea level (CAT 0) max. 3,000 m above sea level (CAT II and CAT III)
Pollution degree	4
Storage temperature	-40 °C to +125 °C
<b>Conformity</b>	<b>CE</b>
<b>Device safety</b>	EN 61010-1:2010 + A1:2019 + A1:2019/AC:2019 with EN IEC 61010-2-030:2021 + A11:2021

<sup>1</sup> Further information can be found in the technical Information document on the subject of "Deviation of Measurement".

<sup>2</sup> Please also read the CSM document "Safety Instructions HV TH4 evo CAN MM"

<sup>3</sup> According to EN 61010-1:2010 + A1:2019 + A1:2019/AC:2019 with EN IEC 61010-2-030:2021 + A11:2021

<sup>4</sup> Further information can be found in the Technical Information document "Measurement Categories for CSM HV Measurement Modules".

<sup>5</sup> Optionally available in other variants



**CSM GmbH**

Raiffeisenstr. 36  
70794 Filderstadt  
Germany

Technical Questions:  
[www.csm.de/service-and-support](http://www.csm.de/service-and-support)

Sales Contact:  
[www.vector.com/contact](http://www.vector.com/contact)

Part of the Vector Group



All trademarks mentioned are property of their respective owners.  
Specifications are subject to change without notice.  
CANopen® and CiA® are registered community trademarks of CAN in Automation e.V.  
EtherCAT® is registered trademark and patented technology,  
licensed by Beckhoff Automation GmbH, Germany.