


K902 SC, R2P 8p, open

Connection cable between an HV analog measurement module and four sensors with measurement voltages up to 90 V



Description

Connection cable between an HV analog measurement module and four sensors (without sensor supply). Shielding per channel for suppressing interferences.

Each cable was subject to an isolation test according to EN 61010-1:2010 before delivery.

Technical data

Diameter	7.4 mm
Strip lengths	
Outer sheath	122 mm
Wire jacket	22 mm
Open cable end	2 mm (tinned)
Operating temperature range	-40 °C to +125 °C, pressure resistance until about +80 °C

Connectors

A Plug LEMO Redel 2P 8-pole code BB 4 × open cable end, 2 wires + shield each

Variants

Article number	Cable number	Length
ART1423803	K902-0200	2 m
ART1423804	K902-0300	3 m

NOTE!



Since cables are often exposed to chafing on bodywork parts, this cable disposes over a multistage safety concept.


- ▶ The **orange outer sheath** provides high mechanical and electrical safety.
- ▶ If the underlying **blue intermediate sheath** becomes visible, this indicates that the cable is no longer mechanically safe. The operational safety is put at risk upon further mechanical stress.
- ► The inner **orange wire jackets** still belong to the area protected against accidental touch. However, their mechanical robustness is limited.

WARNING!



The open cable end is not protected against accidental touch. Touching the open cable end or a damaged cable sheath bears the risk of life-threatening electrical shocks.

To not touch cable end and damaged cable.



^{*} not connected

CSM GmbH

Computer-Systeme-Messtechnik

Raiffeisenstraße 36 • 70794 Filderstadt • Germany Phone: +49711-77964-20 • Fax: +49711-77964-40 info@csm.de • www.csm.de

All trademarks mentioned are property of their respective owners. This document is subject to change without notice.

K902-xxxx_DS_0100_ENG

www.tuv-sud.com/ms-cert