



# UniCAN 3



## Product description

UniCAN 3 is a microcontroller-based stand-alone data logger with up to 12 CAN bus interfaces for the acquisition of measurement data and ECU information.

With the optional features of UniCAN 3, you are well prepared for future measurement tasks: CSM implements the support of many CAN protocols (CCP, XCP,...) and software extensions (CANsend, CAN stimulation,...), upon request.

An internal GPS module recording position, speed and time as well as a modem for mobile communication and a WLAN module for wireless data transmission allow a wide range of applications.

## Shipping content

- ▶ Data logger UniCAN 3
- ▶ CSMunicnf configuration software (Windows 7, 8, 8.1 and 10), documentation

## Key features


CAN



- ▶ Up to 12 CAN bus interfaces, CAN FD capable
- ▶ 4 digital I/O interfaces
- ▶ Exchangeable CF card up to 64 GB
- ▶ GPS receiver with detached antenna
- ▶ LTE modem (+ UMTS / EDGE / GPRS) and WLAN module with detached antenna and Ethernet for
  - ▶ data transmission parallel to recording
  - ▶ remote maintenance (configuration & firmware updates)
- ▶ Very low power consumption (operation & stand-by)

## Accessories

- ▶ See data sheet "UniCAN Accessories"

## Technical data

|                                    |  |
|------------------------------------|--|
| <b>Type designation</b>            | <b>UniCAN 3</b>  |
|                                    |   |
| CAN interfaces                     | 4 × / 8 × / 12 × CAN 2.0B<br>High-Speed CAN (ISO11898-2:2016), max. 2 Mbit/s<br>CAN FD capable, can be enabled via option              |
| Digital inputs/outputs             | 4 × (each channel individually configurable as input or output)  |
| USB                                | 1 × USB 2.0 OTG  |
| LAN                                | 1 × Fast Ethernet 10/100 MBit/s Auto MDI-X   |
| Storage capacity                   | 1 × CF card slot (up to 64 GB)   |
| <b>Available options</b>           |  |
| Hardware                           |  |
| CAN FD                             | CAN FD support according to ISO11898-1:2015  |
| GPS                                | internal GNSS module, 72 channel GPS positioning engine (+ GLONASS / BeiDou / Galileo), 10 Hz position update rate                     |
| Mobile communication <sup>1)</sup> | internal LTE modem (+ UMTS / EDGE / GPRS),   |
| WLAN                               | internal WLAN module (IEEE 802.11 a/b/g/n/ac)  |
| Data upload                        | transfer of raw data to server,<br>further processing with CSMdataconv software<br><a href="#">▶ see section „additional products“</a> |
| Protocols on CAN                   | CCP, XCP, CCP Block Read, OBD2/EOBD, J1939   |
| Software extensions                | CANsend, CAN Stimulation, Wake-on-CAN, Seed & Key (customer-specific adaptation)   |
| <b>Power supply</b>                |  |
| Minimum                            | 8 V DC (-10 %)   |
| Maximum                            | 32 V DC (+10 %)  |
| Power consumption                  | typ. 3 W (in normal operation),<br>max. 6.7 W (at full load)   |
| Standby current                    | PowerControl OFF   |
| w/o Wake-on-CAN                    | < 350 µA at 12 V   |
| 1 × Wake-on-CAN                    | < 450 µA at 12 V   |
| 12 × Wake-on-CAN                   | < 800 µA at 12 V   |

|   |  |
|---|--|
| <b>Type designation</b>                   | <b>UniCAN 3</b>  |
| <b>Indicators</b>                         |  |
| Front side                                | two-digit numerical status display for device status and error codes                               |
| Front & back side                         | 2 multi-color LEDs each for status / network indication / card access                              |
| <b>Housing</b>                            | aluminum, black coated   |
| Weight                                    | approx. 600 g  |
| Dimensions (w × h × d)                    | approx. 109 × 45 × 158 mm  |
| <b>Connectors</b>                         |  |
| CAN                                       | 1 × / 2 × / 3 × D-SUB HD plug, 15-pole<br>(each for 4 × D-SUB connector, 9-pin, via adapter cable) |
| Digital I/O                               | LEMO 0B, 7-pole, code A  |
| Power supply, Ethernet                    | LEMO 0B, 7-pole, code B  |
| USB                                       | Micro-AB USB connector   |
| GPS                                       | FAKRA connector, code C, blue  |
| Mobile communication                      | FAKRA connector, code D, bordeaux  |
| WLAN                                      | RP-SMA connector   |
| <b>Operating and storage conditions</b>   |  |
| Operating temperature range <sup>1)</sup> | -40 °C to +80 °C   |
| Relative humidity                         | max. 95 % (non-condensing)   |
| Storage temperature                       | -40 °C to +85 °C   |
| <b>Certification</b>                      |                 |
| <b>Conformity</b>                         |                 |

<sup>1</sup> The operating temperature of UniCAN 3 versions with integrated modem should not drop below -30 °C. The modem may otherwise not start up reliably.

## additional products

### CSMdataconv

The software **CSMdataconv** is installed on a Windows® server. The **UniCAN 3** data logger then delivers the recorded measurement data, e.g. via mobile data transmission (mobile communications or WLAN) to an FTP or SFTP server which the software can access. **CSMdataconv** then converts the data into the desired format, e.g. MDF or CSV, and makes it available for analysis and post-processing.





## **CSM Products, Inc.**

1920 Opdyke Court, Suite 200 • Auburn Hills, MI 48326 • USA  
Phone: +1 (248) 836-4995 • Fax: +1 (248) 836-4997  
info@csmproductsinc.com • www.csmproductsinc.com

